

FIXING INSTRUCTIONS

- 1) Prior to commencing any fixings it is recommended to layout the rails and work out the positions at which the lights can be used to their maximum potential, remembering that the mobile rails can travel laterally as well as forward and back: Decreasing the space between the fixed rails will increase the lateral travel, but will also increase the load on the fixed rails when the heads are at the ends of the mobile rails.
- . 2) Fix plates to ceiling as below: Initially leave plenty of thread on the screws available so that plates are firmly fixed, but still loose so that rails can be inserted easily and repositioned prior to final tightening.
NB If rails to be fixed to ceiling have only one hole at each end, ensure the hole is on the BOTTOM of the rail Screw Rail
- . 3) Slide double swivels onto Fixed rails, and ensure end stops are in place on lower section of fixed rails (End stops not required on top section of fixed rails BUT are required on lower half).
- . 4) Slide Mobile rails onto the double swivels and ensure the top end stops are in place. Gently test the fixing of the rails before attempting to add pantographs and flash heads. If in any doubt, re-fix the fixed rails.
- . 5) Slide the pantographs onto the bottom of the mobile rails and ensure end stops are in place. Check movement of the system does not cause any collision with anything: Adjust position of end stops to restrict travel if necessary.
- . 6) Fit Flash head to bottom of pantograph. *Use safety cable between head and pantograph.*

Studio Answers Ltd, Church View House, Hillside Farm,
Great Wolford, Warwickshire, CV36 5NQ

Tel: 01608 674984 Email: info@LuxS.biz WWW.LuxS.biz

LuxS